

---

**Material Safety Data Sheets**  
**For Multi Walled Heat Shrink Tubing - Colors**

DOCUMENT: 58238 (Rev. 2)

ISSUED: January 2, 2008

PAGE: 1 of 4

---

| <b>1. INGREDIENT</b>             | <b>C.A.S. NUMBER</b> | <b>PERCENT</b> |
|----------------------------------|----------------------|----------------|
| Adhesive Lined Polyolefin Tubing | Unknown              | 100            |

---

**2. PHYSICAL DATA**

---

|                      |                               |
|----------------------|-------------------------------|
| BOILING POINT:       | N/A                           |
| VAPOR PRESSURE:      | N/A                           |
| VAPOR DENSITY:       | N/A                           |
| EVAPORATION RATE:    | N/A                           |
| SOLUBILITY IN WATER: | N/A                           |
| SP. GRAVITY:         | 1:0                           |
| PERCENT VOLATILE:    | N/A                           |
| PH:                  | N/A                           |
| VISCOSITY:           | N/A                           |
| MELTING POINT:       | N/D                           |
| APPEARANCE AND ODOR: | Tubing, various sizes, colors |

---

**3. FIRE AND EXPLOSION HAZARD DATA**

---

|                           |     |
|---------------------------|-----|
| FLASH POINT:              | N/A |
| FLAMMABLE LIMITS – LEL:   | N/A |
| FLAMMABLE LIMITS – UEL:   | N/A |
| AUTOIGNITION TEMPERATURE: | N/D |

**EXTINGUISHING MEDIA:**

Carbon dioxide, dry chemical, foam

**SPECIAL FIRE FIGHTING PROCEDURES:**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

None known.

**NFPA HAZARD CODES:**

Health: 0 Fire: 0 Reactivity: 0

**UNUSUAL REACTION HAZARD:**

None.

**OSHA FIRE HAZARD CLASS:**

Not applicable.

---

## MULTI WALLED HEAT SHRINK TUBING

January 2, 2008

Page 2 of 4

---

### 4. REACTIVITY DATA

---

**STABILITY:**

Stable.

**INCOMPATIBILITY – MATERIALS TO AVOID:**

None known.

**HAZARDOUS POLYMERIZATION:**

Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Carbon Monoxide and Carbon Dioxide, Oxides of Sulfur, Aldehydes, Toxic Vapors, Gases or Particulates.

Heating product beyond temperature recommended by instruction sheet may cause release of the following compounds: Benzene, Toluene, Formaldehyde, Acetaldehyde, Acetic Acid and Vinyl Acetate.

---

### 5. ENVIRONMENTAL INFORMATION

---

**SPILL RESPONSE:**

Not applicable.

**RECOMMENDED DISPOSAL:**

Dispose of waste product in a sanitary landfill.

**ENVIRONMENTAL DATA:**

No data available.

**REGULATORY INFORMATION:**

Volatile Organic Compounds: N/A  
VOC less H<sub>2</sub>O & Exempt Solvents: N/A

Since regulations vary, consult applicable regulations or authorities before disposal.

**EPCRA HAZARD CLASS:**

**FIRE HAZARD:** No  
**PRESSURE:** No  
**REACTIVITY:** No  
**ACUTE:** No  
**CHRONIC:** No

---

## MULTI WALLED HEAT SHRINK TUBING

January 2, 2008

Page 3 of 4

---

### 6. SUGGESTED FIRST AID

**EYE CONTACT:**

Immediately flush eyes with large amounts of water. Get immediate medical attention.

**SKIN CONTACT:**

Immediately flush affected area with plenty of cold water and cover with a clean dressing. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Have burn treated by a physician.

**INHALATION:**

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

**IF SWALLOWED:**

Drink two glasses of water. Call a physician.

---

### 7. PRECAUTIONARY INFORMATION

**EYE PROTECTION:**

AVOID EYE CONTACT WITH VAPORS OR SMOKE RESULTING FROM OVERHEATING OR WHEN USED IN CONFINED AREAS.

**SKIN PROTECTION:**

Avoid skin contact with hot material. Wear appropriate gloves, such as Nomex, when handling this material to prevent thermal burns.

**VENTILATION PROTECTION:**

Local exhaust is required for operations using large amounts of material. Conduct air monitoring to determine adequacy of ventilation. Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

WHEN USING THIS PRODUCT IN A CONFINED SPACE OR WHERE VENTILATION MAY BE INADEQUATE THEN RESPIRATORY PROTECTION MAY BE WORN. INADEQUATE VENTILATION OR CONFINED SPACES WOULD CAUSE VAPORS FROM HEATING OF THIS PRODUCT TO BE PRESENT IN THE USER'S BREATHING ZONE AND MAY CAUSE RESPIRATORY IRRITATION. EXCESSIVE HEATING OF THIS PRODUCT BEYOND THE RECOMMENDED APPLICATION TEMPERATURE OF 275 DEGREES FAHREHEIT IS NOT RECOMMENDED AND MAY RESULT IN THERMAL DEGRADATION AND DECOMPOSITION PRODUCTS WHICH MAY RESULT IN ADVERSE HEALTH EFFECTS.

**RESPIRATORY PROTECTION:**

Avoid breathing of fumes. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half-mask organic vapor respirator with dust/mist prefilter.



Master Appliance Corporation  
2420 18<sup>th</sup> St Racine WI 53403  
PO Box 68 Racine WI 53401  
Tel 262-633-7791 Fax 262-633-9745  
e-mail sales@masterappliance.com

---

## MULTI WALLED HEAT SHRINK TUBING

January 2, 2008

Page 4 of 4

---

### 7. PRECAUTIONARY INFORMATION (continued)

---

**PREVENTION OF ACCIDENTAL INGESTION:**

Wash hands after handling and before eating.

**RECOMMENDED STORAGE:**

Store at room temperature. Keep out of reach of children.

**FIRE AND EXPLOSION AVOIDANCE:**

Not applicable.

**EXPOSURE LIMITS:**

|                     |                                  |              |      |
|---------------------|----------------------------------|--------------|------|
| <b>INGREDIENTS:</b> | Adhesive Lined Polyolefin Tubing | <b>TYPE:</b> | None |
| <b>VALUE:</b>       | None                             | <b>AUTH:</b> | None |
| <b>UNIT:</b>        | None                             | <b>SKIN:</b> | *    |

\* **SKIN NOTATION:** Listed substances indicated with "Y" under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airbourne or more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

**SOURCE OF EXPOSURE LIMIT DATA:**

AIHA: American Industrial Hygiene Assoc. Workplace Environmental Exposure Level

None: None established.

---

### 8. HEALTH HAZARD DATA

---

**EYE CONTACT:**

Vapors from heated material may cause eye irritation.

**SKIN CONTACT:**

Skin burns (thermal, from contact with hot material): signs/symptoms can include burning pain, red and swollen skin and blisters.

**INHALATION:**

Vapors of heated material may cause respiratory system irritation.

RESPIRATORY IRRITATION WOULD NOT BE EXPECTED IN APPLICATIONS WHERE ADEQUATE VENTILATION AND PROPER APPLICATION (AT DESIGNATED TEMPERATURES) IS UTILIZED. EXCESSIVE HEATING AND INADEQUATE VENTILATION MAY RESULT IN EXPOSURE TO THERMAL DEGRADATION AND DECOMPOSITION PRODUCTS AS INDICATED IN SECTION 4 OF THIS MSDS UNDER "REACTIVITY DATA-HAZARDOUS DECOMPOSITION PRODUCTS".

**IF SWALLOWED:** Ingestion is not a likely route of exposure to this product.